

Specification

Model No.	PD-IEC081500-SM	PD-IEC082000-SM	PD-IEC081600-SM
Power Rating/ Frequency	15A, 125VAC (UL 12A, 100-250VAC) 50/60Hz	20A, 125VAC (UL 16A, 100-250VAC) 50/60Hz	16A, 200 - 250VAC 50/60Hz
Output Receptacle Type	8 x IEC320 Combo Sockets (C13/15/19/21 Combination Sockets)		
Input Type	IEC320 C20 inlet		
Input Phase	Single Phase		
Finish	Black		
Front Display	Color LCD Display		
Mount Orientation	Horizontal		
Height	1U		
Network Connectivity	Yes		
Touch Screen Display	Yes		
Metered per Outlet	Yes		
Switched per Outlet	Yes		
Overload Protection	Yes		
Outlet Scheduling	Yes		
Outlet Power Indicator	Indicating on TFT LCD		
Status Monitoring	Outlet current value warning can be set manually		
IP	Dynamic IP / Static IP		
Daisy Chain Ports	USB x 2; One in one out		
Ethernet Port	RJ45 x 1 with Ethernet Indicator; Gigabit Ethernet:10/100M		
Firmware Update Port	USB 2.0		
Operating Environment	0~50°C		
Physical Dimensions	L.481.0 x W.44.2 x D.200.0 mm		
Safety Approvals	UL/CSA 62368-1 FCC Part 15 Subpart B, ICES-003 Issue 7	UL/CSA 62368-1 FCC Part 15 Subpart B, ICES-003 Issue 7	IEC 62368-1, EN IEC 62368-1 EN 55032, EN 55035 EN IEC 61000-3-2 EN IEC 61000-3-3