

Ahoku Electronic Company

5F, No.88, Sec.1, Nei-Hu Rd., Taipei, Taiwan Tel:+886-2-2799-1199 Fax:+886-2-2799-9099

Specification

Uninterruptible Power Supply UPS-1000DC

Power Rating

Input Voltage (AC) : 100~250VAC, 47~63Hz

Output Voltage (DC) : 13.5VDC(Normal), 12.0VDC(Min.) / 14.2VDC(Max.) --- Utility Power

10.5VDC(Min.) / 14.2VDC(Max.) --- Battery Power

Rated Output Power : 20Watts Max.

Working Efficiency : $\geq 70\%$ at rated output (not in charging condition)

Battery Working Time : 10 minutes max. (@20W Load)
AC-Battery Transfer Time : 0-Second. On Line Transfer

Battery

Type : NI-MH Batteries
Capacity : 12 VDC, 600mAh
Normal Charging Time : Around 8 Hours

Indicator

Utility /Battery Power : LED Indicator (Red) / (Green)

Surge Protection Status : LED Indicator (Green)

Protection Feature

AC Power Surge Protection : Yes
Short Circuit Protection : Yes
Over Load Protection : Yes
Over Voltage Protection : Yes
Low Battery Protection : Yes
Charging Protection : Yes

Environment

Operation Temperature : -5° C \sim 45 $^{\circ}$ C Storage Temperature : -15° C \sim 50 $^{\circ}$ C Operation Humidity : $10\%\sim$ 90%

Dimension

 $L \times D \times H$: 200 x 83 x 70.5 (mm)